

Specifications:

| | |
|------------------------------|--|
| Type of vessel | Multi purpose vessel |
| Class | Bureau Veritas |
| Trading area | Unrestricted navigation |
| Flag | The Netherlands |
| Main dimensions | 32,0 x 11,1 x 3,7 m |
| Minimum operational draught | Approx. 2,4 m |
| Gross tonnage | 314 |
| Propulsion | Twin screw, 5-blade fixed pitch props ø1650 mm |
| Output main engines | 1940 kW |
| Bow thruster | 358 kW – 360 degrees |
| Bollard pull approx. | 31 ton |
| Free running speed | 12 knots |
| Generator | 2x 180 kVA (parallel configuration) |
| Towing/anchor handling winch | 1x 80 ton pull (constant tension), 110 ton hold 1x 45 ton pull (constant tension), 65 ton hold |
| Towing pins | WKH 1500 |
| Auxiliary winch | 1x 10 ton pull All winches controlled from wheelhouse |
| Hydraulic crane | 200 tm |
| Bunker capacities | Fuel 149 m ³ (transfer cap. approx. 90%) Water 43 m ³ (transfer cap. approx. 90%) Sewage 17,5 m ³ |
| Transfer pump | Fuel: 75 m ³ /hr at 3 bar, water: 55 m ³ /hr at 2 bar |
| Accommodation | 2 Cabins 1 person, 3 cabins 2 persons Mess room, galley, sanitary, central heated, air conditioning |

